




CI-700 series

Housing General Specification

- Construction: Die Casting aluminum
- External Dimension: 403 L x 128.7W x 127.5 (H) mm
- Weight: 2900G (with Bracket)
- Operating temperature: -30°C~50°C
- Heater option: 15°C On,25°C Off (10W or 20W)
- PB-700 heater operation: 4°C On, 15°C Off
- Defroster option: 9.5W
- Fan option: 35°C On,25°C Off (12VDC input, 1.8W)
- Certificated: IP66, IK10, CE, FCC, RoHS



Model	Picture	Feature
CI-700		<ul style="list-style-type: none"> - Outdoor Housing for universal cameras - Compatible, powered by 12VDC, 24VAC and 230VAC input
CI-700 PoE		<ul style="list-style-type: none"> - Outdoor Housing with IEEE 802.3af and IEEE 802.3at compliant PoE - Allowing single-cable installation with PoE camera to PoE switch and injector - Powered by 15W, 30W, and 60W PoE input
PB-700		<ul style="list-style-type: none"> - Outdoor Housing supported full-range AC input by friendly installation - Powered by 96VAC~264VAC input and output 70W (5.83A)

Available options

	Sunshade	IR	Heater	Defroster	Fan
CI-700	✓	-	✓	-	✓
CI-700 PoE	✓	-	✓	✓	✓
PB-700	✓	-	✓	✓	✓