MASSLOAD
財榮壓鑄股份有限公司



CI-707

Outdoor Mobility and Fixed ANPR Enclosure

This is an ANPR/ LPR camera enclosure with sleek design for the mobility and fixed type application, which can be easily strongly mounted on a rooftop of a patrol car or installed to the infrastructure.
A heavy-duty design that is comparable to fixed ANPR camera and with IP68 rated, Anti-fog window, IK10 impact resistance, and NEMA-4X (200 hours salt-spray duration) criteria endures all environmental challenges.




Certificated: IP68 – ROHS – IK10 – CE – FCC – NEMA-4X


Technical Specifications


Viewing Window	4mm Tempered PC with Anti-Fog against IK10 impact (View area L148 x H56mm)
Body Construction	Die Casting Aluminum
Mounting Bracket	Aluminum Fixed Cable Management Bracket
Sunshade	Adjustable Aluminum construction
Heater (optional)	15°C On, 25°C Off (10W)
Coating	Powder Black in body, Grey in sunshade& Bracket
Connector	IP68 cable gland
Application	Single Lens: High Power 16mm LED x 18pcs Dual Lens: High Power 16mm LED x 9pcs
3-Axis Mounting Tilt	Up 15 degree & Down 15 degree
Magnet (optional)	Only suitable for the speed under 60KM (37MI)
Operating Temperature	-30°C ~ 70°C


External Dimensions (No Bracket)	L195 x W204.3 x H91.9mm (L7.68" x W8.04" x H3.62")
Internal Dimensions for camera	L100 x W148 x H65mm (L3.94" x W5.83" x H2.56")
Weight (No Bracket)	1.5 kgs (3.3 lbs)

Dimensions









www.massload.com.tw